

Hangzhou Penno Packtech

No4, Yangcheng Road, Fengdu Industrial Zone,
Pingyao Town, Yuhang District, Hangzhou,
Zhejiang, China.

Phone: 86-571-88731169 Fax: 86-571-88734708

www.guoli-packing.com - Email: sales@guoli-packing.net



IMPORT-EXPORT CERTIFICATE

January - December 2016

PENNO Presswood Pallets are essentially reconstituted wood, the same as particleboard, fiberboard or chipboard technology. Fine wood particles are first dried in a hot gas stream with a decreasing temperature from 648 celsius degrees to 138 celsius degrees over a time period exceeding 30 minutes and then mixed with a thermo set synthetic resin, deposited in a heat compression mold with 220 celsius degrees temperature and pressed under 1400PSI or 98 bar pressure. During this process, the pallet will receive an internal temperature of 105celsius degrees and will maintain an internal temperature in excess of 56 celsius degrees for more than 30 minutes. The finished pallet will have a moisture content of not more than 9%. This manufacturing process will destroy any resident pest, insect, molds or fungi. Due to the high density wood paroduct produced, the finished products are resistant to any wood boring insects and future infestation.

This Penno Presswood Pallet is made from reconstituted wood and is a newly wood packaging material and therefore is not considered a solid wood packaging material. This Penno Presswood Pallet is exempt and does not require additional treatment for infestation or stamping on the pallet according to the IPPC and ISPM15.

Signed by:

Date:

Export shipper's Information

No of pallets	vessel
Consignee	container
country of ultimate destination	Air or sea BOL
Invoice No	agent's signature
Date	title

